

Contempo Aluminium Framed Doors

Double Glazed - Specification Overview



FRAMING DIMENSIONS:

Face bonded 6mm safety glass with a 63mm back painted border covering the 63mm x 32mm aluminium perimeter frame.

ACOUSTICS PERFORMANCE:

2 x 6mm toughened safety glass with drop down threshold and full perimeter seals - Rw 41dB.

INTEGRATION:

The door will fully integrated with all Fusion glazed partitioning systems and both the 75mm and 100mm plasterboard partition wall systems.

COLOUR FINISH:

Polyester powder coated in any BS4800 or RAL colours available to order. A selection of anodised and other special finishes are also available to order.

MANIFESTATION:

To meet the requirements of Part M of the Building Regulations (*minimum 50mm dots @ 100mm centres*) or to clients specification using Digital printed logos / graphics on film, screen printed or acid etched glass.

DOOR FRAMES:

A range of acoustic performance enhancing single or double glazed aluminium, natural timber and MDF veneered door frames.

IRONMONGERY:

Range of offset top and bottom hinges, top and bottom pivots complete with floor spring (BTS75) or 100mm stainless steel Lift Off hinges that are complemented by a range of satin or polished stainless steel finished lever sets, pull handles and patch locks,

DRAWINGS & PHOTOGRAPHS:

Detailed junction drawings and a selection of installation photographs can be viewed on our web site www.fusionpartitions.com